



## 2022-2020 STRING AND CABLE LENGTHS

NEW  
NEW  
NEW  
NEW

2022 MODEL	STRING	CABLE 1	CABLE 2	AXLE TO AXLE	BRACE HEIGHT
SR350	63.42	38.375		33"	6"
CP-28	59.875	33.4		28"	6 3/4"
RevoltXL	65.86	38.313		33"	6.5"
RevoltX80	63.313	42.42		33"	6.5"
SOLUTION	61	37.41		32	6
SOLUTION SS	61.875	35.4		30	7
SOLUTION SD	55.375	35.438		30	7
EVA GEN 2	55.375	35.438		30	7
ZION/DLX	56.82	37.07		31	6.5
AMPLIFY	57.7	38.335		31 1/2	6
SPECIALIST II	62.875	45.375		38	7 1/8
RECKONING 38	65.313	42.420		38	7 1/8
RECKONING	62.31	39.42		35	7
2021 MODEL	STRING	CABLE 1	CABLE 2	AXLE TO AXLE	BRACE HEIGHT
SOLUTION	61	37.41		32	6
SOLUTION SS	61.875	35.4		30	7
SOLUTION SD	55.375	35.438		30	7
EVA GEN 2	55.375	35.438		30	7
ZION/DLX	56.82	37.07		31	6.5
AMPLIFY	57.7	38.335		31 1/2	6
REVOLT	60.156	35.375		30	7 1/4
REVOLT X	63.313	38.313		33	6 1/2
SPECIALIST II	62.875	45.375		38	7 1/8
RECKONING 38	65.313	42.420		38	7 1/8
RECKONING	62.31	39.42		35	7
2020 MODEL	STRING	CABLE 1	CABLE 2	AXLE TO AXLE	BRACE HEIGHT
REVOLT	60.156	35.375		30	7 1/4
REVOLT X	63.313	38.313		33	6 1/2
SPECIALIST II	62.875	45.375		38	7 1/8
RECKONING 38	65.313	42.420		38	7 1/8
GUARDIAN	60.67	33.72		30 3/4	7 1/8
RECKONING	62.31	39.42		35	7
REALM SR6	59.88	33.75		32	6
REALM SS	62.81	35.19		32	6
BT-MAG X	69.81	39.69		36	7
EVA SHOCKEY SIGNATURE SERIES	57.25	34.28		31 1/2	6 1/4



## 2019-2018 STRING AND CABLE LENGTHS

CARBON ICON	55.59	35.5		31	7
CARBON ROSE	51.13	33.81		30	6 3/4
CONVERGENCE	57.72	38.34		31 1/2	7
<b>2019 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
RECKONING	62.31	39.42		35	7
REALM SRG	59.88	33.75		32	6
REALM SS	62.81	35.19		32	6
REALM	60.67	33.72		30 3/4	7 1/8
REALM X	63.08	36.13		33 1/4	6 1/2
BT-MAG X	69.81	39.69		36	7
FANATIC 3.0 29"	56.3	40.66		37 3/4	7
FANATIC 3.0 32"	62.65	40.66		37 3/4	7 3/8
EVA SHOCKEY SIGNATURE SERIES	57.25	34.28		31 1/2	6 1/4
CARBON ICON	55.59	35.5		31	7
CARBON ROSE	51.13	33.81		30	6 3/4
CONVERGENCE	57.72	38.34		31 1/2	7
<b>2018 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
REALM	60.67	33.72		30 3/4	7 1/8
REALM X	63.08	36.13		33 1/4	6 1/2
BT-MAG X	69.81	39.69		36	7
REIGN 6	62.13	35.19		32 5/8	6
REIGN 7	62.13	35.19		32 5/8	7
BT-MAG	65.38	39		36	6 3/4
BT-X 31"	64.25	34.56		31	6 1/4
BT-X 28"	60.44	34.13		31	6
FANATIC 3.0 29"	56.3	40.66		37 3/4	7
FANATIC 3.0 32"	62.65	40.66		37 3/4	7 3/8
BOSS	64.25	39.25		36	7
EVA SHOCKEY SIGNATURE SERIES	57.25	34.28		31 1/2	6 1/4
CARBON ICON	55.59	35.5		31	7



## 2017-2015 STRING AND CABLE LENGTHS

CARBON ROSE	51.13	33.81		30	6 3/4
FUEL	55.56	36.09		31 1/2	7 1/8
<b>2017 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
REIGN 6	62.13	35.19		32 5/8	6
REIGN 7	62.13	35.19		32 5/8	7
BT-MAG	65.38	39		36	6 3/4
BT-X 31"	64.25	34.56		31	6 1/4
BT-X 28"	60.44	34.13		31	6
FANATIC 3.0 29"	56.3	40.66		37 3/4	7
FANATIC 3.0 32"	62.65	40.66		37 3/4	7 3/8
PRODIGY	60.5	35.31		32	7
BOSS	64.25	39.25		36	7
EVA SHOCKEY SIGNATURE SERIES	57.25	34.28		31 1/2	6 1/4
CARBON ICON	55.59	35.5		31	7
CARBON ROSE	51.13	33.81		30	6 3/4
FUEL	55.56	36.09		31 1/2	7 1/8
<b>2016 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
BT-X 31"	64.25	34.56		31	6.25
BT-X 28"	60.44	34.13		31	6
PRODIGY	60.5	35.31		32	7
BOSS	64.25	39.25		36	7
FANATIC 2.0 29"	56.05	40.41		37.5	7.13
FANATIC 2.0 32"	62.4	40.41		37.5	7.38
EVA SHOCKEY SIGNATURE SERIES	57.25	34.28		31.5	6.25
CARBON ICON	55.59	35.5		31	7
CARBON ROSE	51.13	33.81		30	6.75
FUEL	55.56	36.09		31.5	7.125
<b>2015 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
PRODIGY	60.5	35.31		32	7
BOSS	64.25	39.25		36	7



## 2014-2013 STRING AND CABLE LENGTHS

FANATIC	59.69	39.34		36.5	7.75
RPM 360	61.16	34.2		31	6
CARBON OVERDRIVE	59.69	34.88		31.5	6.5
EVA SHOCKEY SIGNATURE SERIES	57 1/4	34 9/32		31.5	6.25
CARBON ICON	55 19/32	35 1/2		31	7
CARBON ROSE	51.13	33.81		30	6.75
FUEL	55 9/16	36 3/32		31.5	7.125
<b>2014 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
RPM 360	61 5/32	34 13/64		31	6
CARBON OVERDRIVE	59 11/16	34 7/8		31.5	6.5
EXPERIENCE	60 7/32	34 15/16		32	7
INSANITY CPXL	63 1/4	37 15/16		35	7
SPECIALIST	60 11/16	40		37 7/16	7 1/2
CARBON KNIGHT	57 3/8	35 7/16		31	7
CARBON ROSE	51.13	33.81		30	6.75
FUEL	55 9/16	36 3/32		31.5	7.125
<b>2013 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
EXPERIENCE	60 7/32	34 15/16		32	7
INSANITY CPX	60 1/8	34 29/32		32	6
INSANITY CPXL	63 1/4	37 15/16		35	7
SPECIALIST	60 11/16	40		37 7/16	7 1/2
ASSASSIN	55 7/16	36 5/8		30 5/8	7
HEARTBREAKER	50 1/16	33 7/8		30 1/4	7 1/8



## 2012-2009 STRING AND CABLE LENGTHS

2012 MODEL	STRING	CABLE 1	CABLE 2	AXLE TO AXLE	BRACE HEIGHT
INSANITY CPX	60 1/8	34 29/32		32	6
INSANITY CPXL	63 1/4	37 15/16		35	7
INVASION CPX	58 9/32	34 5/16		31 1/32	7 1/8
SPECIALIST	60 11/16	40		37 7/16	7 1/2
ASSASSIN	55 7/16	36 5/8		30 5/8	7
ASSASSIN SD	50 1/16	33 7/8		30 1/4	7 1/8
HEARTBREAKER	50 1/16	33 7/8		30 1/4	7 1/8
2011 MODEL	STRING	CABLE 1	CABLE 2	AXLE TO AXLE	BRACE HEIGHT
INVASION CPX	58 9/32	34 5/16		31 1/32	7 1/8
SPECIALIST	60 11/16	40		37 7/16	7 1/2
DESTROYER 350	61 9/16	35 5/8		32 3/8	6
DESTROYER 340	61 9/16	35 1/2		32 3/8	7
ASSASSIN	55 7/16	36 5/8		30 5/8	7
HEARTBREAKER	50 1/16	33 7/8		30 1/4	7 1/8
SOLDIER	52 13/16	35 3/4		31 3/8	6 7/8
2010 MODEL	STRING	CABLE 1	CABLE 2	AXLE TO AXLE	BRACE HEIGHT
DESTROYER 350	61 9/16	35 5/8		32 3/8	6
DESTROYER 340	61 9/16	35 1/2		32 3/8	7
ADMIRAL FLX	57 13/16	35 25/32		31	7 1/2
CAPTAIN	60 11/16	38 11/16		34	7
SENTINEL FLX	63	41 1/4		36 7/16	7
BRIGADIER	61 3/8	43 5/8		40 3/16	8
SWAT	60 1/8	37 5/8		34 1/32	7
AIR RAID 2	91 5/8	35 11/16		33 7/8	6 7/8
SNIPER	60 1/8	37 5/8		34 1/8	7 3/4
SOLDIER	52 13/16	35 3/4		31 3/8	6 7/8
2009 MODEL	STRING	CABLE 1	CABLE 2	AXLE TO AXLE	BRACE HEIGHT
ADMIRAL	57 23/32	35 29/32		31 1/16	7 1/2
CAPTAIN	60 11/16	38 11/16		34	7



## 2008-2006 STRING AND CABLE LENGTHS

SENTINEL	63	41 3/8		36 11/16	7
BRIGADIER	61 3/8	43 5/8		40 3/16	8
82 AIRBORNE	57 1/4	40 15/16		36 1/4	6 1/8
AIR RAID	56 11/16	32 1/16	15 3/4 HARNESS	33 7/8	6 7/8
SWAT	60 1/8	37 5/8		34 1/32	7
SNIPER	60 1/8	37 5/8		34 1/8	7 3/4
<b>2008 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
82 AIRBORNE	57 1/4	40 15/16		36 1/4	6 1/8
101 AIRBORNE	57 1/4	41 7/32		36 5/16	7 1/16
GENERAL	58 3/4	37 3/16		31 3/16	8 1/4
GUARDIAN	56 11/16	38 1/8		33 3/4	7 1/8
COMMANDER	59 3/8	42 3/4		37 3/8	8
ALLEGIANCE	56 3/4	37 1/4		33 3/16	7 1/4
EQUALIZER	51 3/16	37 5/8		33 1/4	7 1/4
CONSTITUTION	58 3/4	45 3/8		41	8 1/4
TOMKAT	53 3/4	36 3/8		31 11/16	8 3/8
<b>2007 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
CONSTITUTION	58 3/4	45 3/8		41	8 1/4
EQUALIZER	51 3/16	37 5/8		33 1/4	7 1/4
TRIBUTE	55 7/32	35 5/16		31 1/2	7 3/4
ALLEGIANCE	56 3/4	37 1/4		33 3/16	7 1/4
TOMKAT	53 3/4	36 3/8		31 11/16	8 3/8
GUARDIAN	56 11/16	38 1/8		33 3/4	7 1/8
COMMANDER	60 3/16	41 5/8		37 1/4	7 1/2
<b>2006 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
TRIBUTE	54 1/8	35 7/8		31 1/2	7 1/2
ALLEGIANCE	56 1/32	38 1/8		34	7
TOMKAT	53 3/4	36 3/8		31 3/4	8 5/8
EQUALIZER	51 11/32	37 1/16		32	7
OLD GLORY	59	41		36 3/4	8
CONSTITUTION	59	44 9/16		40	8 1/4



## 2005-2003 STRING AND CABLE LENGTHS

PBR	91 3/16	36 5/16		34	7 1/4
<b>2005 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
ALLEGIANCE VFT	56 3/16	38 1/8		33 5/8	7
BLACKKNIGHT	55 1/8	38 1/8		36 1/4	5 3/4
CONSTITUTION	62 3/4	44 9/16		40	8 1/4
DEFENDER VFT	53 13/16	35 1/2		31 1/4	7 3/8
INDEPENDENCE	104 3/4	41 15/16		40	7 3/8
JUSTICE VFT	86	33 5/8		31 1/4	8
LIBERTY VFT	89 15/16	35 7/16		33 1/4	7 1/2
MIGHTY MITE VFT	82 3/4	33 1/16		30 5/8	7 5/8
MIRANDA	82 7/8	34 13/32		32 1/2	8 1/4
OLD GLORY	60	41 9/16		37 1/4	7 1/4
PATRIOT VFT	87 15/16	35 3/8		33 1/4	7
PBR	91 3/16	36 5/16		34	7 1/4
RASCAL	66 13/16	26 9/16		24 1/2	7 1/4
TOMKAT	86 5/16	34 7/8		32 1/2	8 1/2
<b>2004 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
BLACKHAWK	79	31 3/8		28 7/8	8
BLACKHAWK 2	74 15/16	31 1/16		29	7 1/2
BLACKKNIGHT	55 1/8	38 1/8		36 1/4	5 3/4
EXTREME VFT	89 1/2	36 1/4		34	6 5/8
JUSTICE VFT	85 3/4	33 1/2		31 1/4	8
LADYHAWK	74 15/16	31 1/16		29	7 1/2
LIBERTY VFT	90 1/8	35 7/16		33 1/4	7 1/2
MIGHTY MITE VFT	82 1/2	33 9/16		30 1/2	7 3/4
PRO 40 SC	98 3/8	40		38 5/8	7 3/4
PRO 40 DUALY	55 3/8	39 3/8		37 1/2	8 1/4
PRO 40 WHEELY	54 3/4	39 1/4		37 1/8	7
PATRIOT VFT	87 1/4	35 7/32		33	7
PATRIOT VFT DUALY	53 3/4	36 7/8		35 1/8	7 5/8
SAMSON VFT	89 1/2	36 1/4		34	6 5/8
TOMKAT	83	33 1/2		31	9 1/8
RASCAL	65 9/16	26 11/16		24 1/2	7 1/4
<b>2003 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
BLACK KNIGHT PRO (SHORT & TALL)	55 9/16	36 7/8		36	5 3/4 or 6 3/4
BLACKHAWK	79	31 3/8		28 7/8	8



## 2002-2001 STRING AND CABLE LENGTHS

EXTREME VFT	89 1/2	36 1/4		34 1/16	6 5/8
GENERATION 3.2	90 1/16	39 5/8	18	38	7
LADYHAWK	73 15/16	30 3/4		29	7 1/2
MIGHTY MITE	84 3/8	33 3/4		31 1/4	7 1/4
PRO 40 SC	98 1/4	41 1/4		38 5/8	7 3/4
PRO 40 DUALLY CAM	56 7/8	38 1/2		38	7 3/8
PRO 40 WHEELY	54 3/4	39 1/4		38	7 1/4
PATRIOT SC	88 9/16	36 1/2		35	7 3/8
PATRIOT DUALLY	54 1/4	35 3/4		34	7 11/16
PRO 38	94 1/4	39 1/4		36 2/3	7 3/8
RASCAL	65 9/16	26 11/16		24 1/2	7 1/4
SAMSON	89 1/2	36 1/4		34	6 5/8
STALKER	87 5/16	35 1/8		33 1/8	7 3/4
STALKERLITE	84 7/8	35 1/2		33 3/4	6 7/8
TECH 29	80 5/8	31 3/4		29 1/2	6 1/2
TOMKAT	83	33 1/2		31	9 1/8
<b>2002 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
BLACKHAWK	78 1/2	31 3/16		23 3/8	9 1/5
BLACKKNIGHT 2	56 1/2	39 3/16		37.5	5.5
EXTREME SOLO (SHORT & TALL)	90 5/8	37 3/16		35	6 or 7
EXTREME SD (SHORT & TALL)	86	35		32 1/2	5 5/8 or 6 5/8
GENERATION 3.2	90 1/16	39 5/8	18	37 1/2	7
MIGHTY MITE	84 3/16	33 11/16		31 1/2	7 1/4
PRO 38 DUALLY	56 1/16	40			
PRO 38 (SHORT & TALL)	95 15/16	39 5/8		37 1/3	6 1/16 or 7 1/16
PRO 40 (SHORT & TALL)	98 3/16	41 1/4		38 1/2	6 3/4 or 7 3/4
PATRIOT	88 5/8	36 7/16		34	7 1/4
RASCAL	65 9/16	26 11/16		24 1/2	7 1/2
SAMSON (SHORT & TALL)	92 9/16	38 1/16		36	5 5/8 or 6 5/8
STALKER	87 7/8	35 1/2		33 1/2	7 3/4
STALKERLITE	84 7/8	35 1/2		33 1/2	
TECH 29	80 7/8	31 7/8		29 1/2	6 1/2
TOMKAT	82 9/16	33 5/8		31	9
<b>2001 MODEL</b>	<b>STRING</b>	<b>CABLE 1</b>	<b>CABLE 2</b>	<b>AXLE TO AXLE</b>	<b>BRACE HEIGHT</b>
BLACKKNIGHT 2 (SHORT & TALL)	55 1/8	38 1/16		36	5 1/4 or 6 1/4
EXTREME SOLO (SHORT & TALL)	92 7/16	38 1/16		36	5 5/8 or 6 5/8
EXTREME SD (SHORT & TALL)	85 7/8	35		32 1/2	5 7/8 or 6 7/8
GENERATION 3 (SHORT & TALL)	87 1/2	38 1/16	18	36	5 5/8 or 6 5/8
MIGHTY MITE	84 3/16	33 11/16		31 1/2	7 1/4